RISK ASSESSMENT

rOD

PRODUCT NAME:	RODEO BUL	L MULTI-RIDE					
RISK DESCRIPTION	WHO MIGHT BE HARMED?	WHAT IS THE RISK?	EXISTING CONTROL MEASURES	RISK SEVERITY	RISK LIKELIHOOD	RISK RATING	NEW CONTROL MEASURES
Loading, handling and transportation of equipment	Operator Spectators	Injuries caused by: Heavy lifting Unacceptable access Injury to Operator or Spectators	All equipment must be handled in correct manner in line with manual handling. Only our staff should move the equipment. Manual handling should be reduced to a minimum by using the trolleys. Ramps & lifts to be used where required and available. All loads must be properly secure.	TOLERABLE	IMPROBABLE	MEDIUM	Where required multiple persons must handle equipment. Individual persons should not undertake anything that puts themselves or anyone else at risk. Manual handling training is supplied to all staff annually. Under no circumstances shall anyone but our staff transport equipment.
Installation of equipment on site	Operator Spectators Participants	Injury caused by: Debris Tripping over equipment Injury to Operator, Spectators or Participants	The operator must have clear access to the setup area. The setup area must be level and free from any rubbish, debris and sharp objects etc. The equipment must be inspected before, during and after installation to ensure it is free from damage.	ACCEPTABLE	IMPROBABLE	LOW	Once installed the item should not be moved by any unauthorized persons. The equipment should be set up away from any entrances or exits ensuring it does not block any fire exits. All anchor points must be used. Any spare equipment must be tidied away and put in a safe place.

Electricity & cabling	Operator Spectators Participants	Injuries caused by: Trips Power cut outs Injury to Operator, Spectators or Participants	The equipment requires access to a 13-amp plug socket. The power socket ideally should be no further than 30 - 40m away from equipment. All electrical components are inspected and PAT every 6 months.	TOLERABLE	IMPROBABLE	MEDIUM	All cabling to be routed away from walkways and any cables crossing footpaths or vehicle access routes to be covered with cable ramps where possible. If area is too large then access should not be used and client should provide cones to block off the area from vehicle access. If power socket is more than 40m away then a generator is advised due to risks caused by trailing cables, however the power can safely be up to 100m away should cable be routed out the way of footpaths and vehicle access.
Operation of equipment on site	Operator Spectators Participants	Injuries caused by: Overcrowding of the area Not following the operator's instructions Injury to Operator, Spectators or Participants	Participants to queue in front of the equipment in view of the operator who will control the queue. Participants not to overcrowd the area and keep a clear space around the item. Always follow the user limitations for the item. Equipment will only be operated by our fully trained staff members. Under no circumstance will anyone untrained be able to operate the ride.	ACCEPTABLE	POSSIBLE	LOW	Spectators should be away from the equipment and not allowed to interfere with the equipment in anyway. Only Live 9 Events Staff can operate this item, staff are trained by a manager for a 6-month period before being able to operate without manager supervision.

User safety	Operator Spectators Participants	Injuries caused by: By other participants Misbehavior Lack of supervision Not following the operator's instructions Choking Injury to Operator, Spectators or Participants	Equipment will only be operated by our fully trained staff members. Under no circumstance will anyone untrained be able to operate the ride. Participants to be aware of their own physical ability and notify the operator if they do not wish to participate or wish to end the activity. No food or drink is allowed on the item. Rules must be followed at all times.	TOLERABLE	IMPROBABLE	MEDIUM	Should any participant appear to be under the influence of alcohol or drugs to the extent where they are posing a risk to the operator or participants, or spectators the operator will close the equipment and seek assistance from the event manager or hirer. The operator reserves the right to refuse admission to anyone they feel may be unsafe to partake in the activity. Only Live 9 Events Staff can operate this item, staff are trained by a manager for a 6-month period before being able to operate without manager supervision.
Injury through improper landing	Spectators Participants	Injuries caused by: Falling onto inflatable bed in an odd way Injury to Spectators or Participants	Equipment will only be operated by our fully trained staff members. Under no circumstance will anyone untrained be able to operate the ride.	TOLERABLE	POSSIBLE	MEDIUM	Participants should sit upright on the rodeo bull face forward and hold onto the rope. An emergency procedure has been put in place in the event of serious injury through improper landing. All of our staff are fully trained in the operation of the ride and emergency procedure.

Injury through bouncing off the inflatable bed	Spectators Participants	Injury to Spectators or Participants	Equipment will only be operated by our fully trained staff members. Under no circumstance will anyone untrained be able to operate the ride.	TOLERABLE	POSSIBLE	MEDIUM	Spectators not to overcrowd the area and keep a clear space around the inflatable surround.
Injury through incorrect set up	Operator Spectators Participants	Injury caused by: Positioning of the inflatable Insufficient anchorage Other incorrect erection procedures	Equipment to be set up by trained staff only. Never use the inflatable without proper anchorage in place. The inflatable must not be altered once set up.	UNDESIRABLE	IMPROBABLE	MEDIUM	Equipment to be set up by trained staff only, all staff are monitored by a manager for a 6-month period before being left unsupervised. All staff attend an in-house annual training course. Once all items are set up a walk around of each inflatable is conducted by the operator.

LIVE 3 EVENISLTD

Injury through equipment defect	Operator Spectators Participants	Injuries caused by: Deflation Equipment integrity	This mutli-ride is tested to EN60-204 Electrical Equipment of Machines. IEE Wiring Regulations 16 th Edition BS 7671. The console has been manufactured in accordance with IS09002. All electrical equipment is inspected and PAT every 6 months.	TOLERABLE	IMPROBABLE	MEDIUM	All equipment has a visual inspection on set up and pack down, any defects are reported to the operator and equipment is taken out of action until required remedial works have been carried out. The user limitations provided by manufacturer to be followed at all times. Our team have procedures in place should deflation occur.
Neck or back injury	Participants	Injuries caused by: By other participants Misbehavior Not following the rules Injury to Participants	Equipment will only be operated by our fully trained staff members. Under no circumstance will anyone untrained be able to operate the ride. All of our staff are fully trained for emergency procedure in case of suspected serious injury.	UNDESIRABLE	IMPROBABLE	MEDIUM	The operator reserves the right to refuse admission to anyone they feel may be unsafe to partake in the activity. The operator reserves the right to close the equipment and seek assistance from the event manager or hirer should a participant pose a risk to the operator or other participants or spectators. In the event that someone is seriously injured, DO NOT move the individual, leave the inflatable switched on and dial 999 immediately.

Weather	Injury to Operator, Spectators or Participants	Injuries caused by: Slippery surface Inflatables taking flight	Equipment should not be used in heavy rain or extreme weather conditions such as winds or gusts above 24 mph. Equipment is suitable for indoor use and can be set up inside a suitable location providing adequate space.	UNDESIRABLE	IMPROBABLE	MEDIUM	All inflatables are supplied with an anemometer to monitor the wind speeds every 30 to 60 minutes. Inflatables should be switched off if wind or gust speeds reach 19 mph. All participants to vacate the equipment when the play area of the inflatable becomes wet and slippery. Inflatable must be not be used until it is dry.
Pressure	Injury to Operator, Spectators or Participants	Injuries caused by: Lack of pressure	The minimum air pressure inside the structural part of the inflatable shall be 1kPA (100mm water gauge).	UNDESIRABLE	IMPROBABLE	MEDIUM	Prior to use and once set up all inflatables are tested with a manometer to give a pressure reading. Pressure reading shall be a minimum of 1kPa, if the reading is less the inflatable will not be used. All staff are trained in how to take a pressure reading using the manometer.

EVENT INNOVATION

Generator and risk of fire	Injury to Operator, Spectators or Participants	Injuries caused by: Fire Heat	Generators are filled with fuel before delivery and must remain a minimum of 5m away from equipment in an off fenced area. Under no circumstances should anyone other than our team enter the fenced off area where the generator is. No smoking or BBQs should be within 5m of the equipment.	UNDESIRABLE	IMPROBABLE	MEDIUM	All hires where generators will be used will be set up with an earth rod and a fire extinguisher provided. All spare fuel is stored in suitable marked containers and in a safe location. All items must be switched off during refueling. Equipment is fire retardant.
----------------------------	---	--	--	-------------	------------	--------	--

The above information is based on manufacturers' criteria and experience from extensive use of the equipment.

Any other action required: This item can only be operated by Live 9 Events staff and all staff will follow the training they have been given. If required can refer to the "Staff Information Pack & Safety Guide".

Risk assessment carried out by: Molly Huthwaite Reviewed Date: 16 June 2023 Signature: M. Huthwaite



EVENT INNOVATION